

ULTRALX® AC90 Armoured Cable

Meeting the following requirements:

- CSA 22.2 No. 51-95 (AC90) for use in Canada



Applications

For use in service, feeder and branch circuits in commercial, industrial, multi-residential buildings and places of assembly. For exposed and concealed wiring in dry locations (90°C).

Intended for installation in accordance with the Canadian Electrical Code Part 1.

Specification

PVC/Nylon Insulated Copper Conductors

14 AWG to 6 AWG (Solid or Stranded) 600 volts

Polyester Tape

Aluminum Interlocking Armour

Smaller OD and Lightweight Construction (*up to 15% lighter than traditional AC90 construction*)

Special Considerations

Multiple Grounding Conductors

Oversized Neutral Conductors

Multi-Conductors (Multi-circuit)

Special requests can be made online at support@electeconline.com or by phone (613) 836-0300

	Product	Circuit	Neutral	Ground	Nom. OD	Weight (lbs/1000')
ULTRALX AC90 Armoured Cable Standard Product Information Solid Copper Conductors 150m reels	14/2	1 - #14 blk	1 - #14 wht	1 - #14 bare	.43"	82
	14/3	2 - #14 blk, red	1 - #14 wht	1 - #14 bare	.45"	101
	14/4	3 - #14 blk, red, blu	1 - #14 wht	1 - #14 bare	.47"	120
	12/2	1 - #12 blk	1 - #12 wht	1 - #14 bare	.45"	96
	12/3	2 - #12 blk, red	1 - #12 wht	1 - #14 bare	.46"	124
	12/4	3 - #12 blk, red, blu	1 - #12 wht	1 - #14 bare	.49"	152
	10/2	1 - #10 blk	1 - #10 wht	1 - #12 bare	.49"	135
	10/3	2 - #10 blk, red	1 - #10 wht	1 - #12 bare	.52"	174
	10/4	3 - #10 blk, red, blu	1 - #10 wht	1 - #12 bare	.56"	215
	14/2 IG	1 - #14 blk	1 - #14 wht	2 - #14 bare, green	.45"	101
	12/2 IG	1 - #12 blk	1 - #12 wht	2 - #14 bare, #12 green	.46"	124
	10/2 IG	1 - #10 blk	1 - #10 wht	2 - #12 bare, #10 green	.52"	174