






































Features and Benefits:

- **ELECTEC EZ-Wiring**[®] components are UL Listed to be in compliance with UL 183 – Manufactured Wiring Systems (QQVX) and CSA Certified to be in compliance with CSA 22.2 No. 203-1- Manufactured Wiring Systems.
- Constructed using **ULTRALX**[®] MC/AC90* cable (300lbs Tension), minimum 12AWG stranded conductors rated 600V 20A.
- Available with SJOW Cord where acceptable.
- Robust terminal design exceeds 470Amp for 4 seconds.
- Eco-Friendly, Low Smoke, V0 rated, RoHS-compliant materials. Dielectric Withstand 3000Vac.
- Connectors are integrally moulded (fully encapsulated) utilizing high impact Halogen-free polymers for superior strength, reliability and safety.
- Mating connectors are self-latching and shrouded for added protection.
- Uniquely-keyed and colour-coded to clearly indicate ratings and provide safe, simple, error-free connectivity. Only connectors having identical colours can plug together properly.
- Approved “Ballast Disconnect Means” per NEC 410.73(g) and CEC Part 1 30-308(4).
- Suitable for use in environmental air handling spaces (plenums) per NEC 300-22(c) and CEC Part 1 12-010(3)
- Acceptable for interrupting current (make or break) under full load.

POWER APPLICATIONS						
125/250V 20A Gray Shell/Cap	3w	4w	5w		7w	
	(L,N,G)	(2L,N,G)	(2L,2N,G)	(3L,N,G)	(3L,3N,G)	(4L,2N,G)
						
	1H-22-1110-R	1H-22-2110-R	1H-22-2210-R	1H-22-3110-R	1H-22-3310-R	1H-22-4210-R
	4w	5w	6w		8w	
	(L,N,2G)	(L2,N,2G)	(2L,2N,2G)	(3L,N,2G)	(3L,3N,2G)	(4L,2N,2G)
						
	1H-22-1120-R	1H-22-2120-R	1H-22-2220-R	1H-22-3120-R	1H-22-3320-R	1H-22-4220-R

	LIGHTING APPLICATIONS					SWITCH		
	Single cct.	Dual/Split cct.	3ph 4w	with Control (Class 1)		1P	c/w Neutral	3 or 4 Way
	(L,N,G)	(2L,N,G)	(3L,N,G)	Single cct.	3ph 4w	(L,G,S)	(L,N,G,S)	(L,N,G,2S)
125/250V 20A Gray Shell/Cap								
	1H-22-1110-R	1H-22-2110-R	1H-22-3110-R	1H-2D-1112-R	1H-2D-3112-R	1H-22-1011-R	1H-22-1111-R	1H-22-1112-R
277/480V 20A Tan Shell/Cap								
	1H-42-1110-R	1H-42-2110-R	1H-42-3110-R	1H-4D-1112-R	1H-4D-3112-R	1H-42-1011-R	1H-42-1111-R	1H-42-1112-R
347/600V 20A Brown Shell/Cap								
	1H-62-1110-R	1H-62-2110-R	1H-62-3110-R	1H-6D-1112-R	1H-6D-3112-R	1H-62-1011-R	1H-62-1111-R	1H-62-1112-R



Front View - Receptacle configuration shown

