

1. BRASS BLADE
2. BRASS GROUND PIN
3. MOULDED THERMOPLASTIC
4. "ULTRALX" AC90/MC or AC90 or MC LS 600V 90°C (CSA 22.2 No. 51–95 and UL 1569)
5. BRASS GROUND TERMINAL
6. BRASS TERMINAL

WHERE "cc" REPRESENTS COLOUR CODE I.E. "BK" IS BLACK
WHERE "d" REPRESENTS CERTIFIED WIRING MATERIAL. I.E. "A" IS AC90
WHERE "lll" REPRESENTS LENGTH CODE I.E. "040" IS 04.0 METERS

SYSTEM IS RATED FOR CONNECTION TO A GROUNDED 125V BRANCH CIRCUIT.

MANUFACTURED WIRING SYSTEM UTILIZING 12 AWG APPROVED ULTRALX CABLE.

INSTALLATION IN ACCORDANCE WITH THE CEC PART I OR THE NEC.

ACCEPTABLE FOR USE IN ENVIRONMENTAL AIR SPACES OTHER THAN DUCTS OR PLENUMS PER CEC PART I 12-010(3) OR NEC 300-22(C)

MEETS OR EXCEEDS: - CSA 22.2 NO. 203.1
- UL 183

ACCEPTABLE MEANS FOR DISCONNECTING LUMINARIES PER CEC PART I 30-308(4) OR NEC 410.73(G).

Manufactured with "AC90/MC" C US

Manufactured with "AC90" LR 91749

Manufactured with "MC" US

125 Volt 20 Amp

CDN. PATENT – 1219307 U.S. PATENT – 4775802

ITEM	DESCRIPTION		PART#/POSITION	REMARKS
4	BARE		1	GROUND
	WHITE		2	NEUTRAL
	BLACK		3	LINE

ELECTEC
100-5977 HAZELDEAN ROAD, OTTAWA, ONTARIO, CANADA K2S 1B9
TELEPHONE (613) 836-0300 FAX (613) 836-0391
TOLL-FREE (866) 233-5328 FAX (866) 933-1933
e-mail: support@electeconline.com

OWNERSHIP OF DOCUMENTS
This drawing and accompanying information as instrument of service are the property of ***ELECTEC***. Reproduction or use in whole or in part in any form whether the work for which they are presented is executed or not is forbidden without the express written permission of ***ELECTEC***.

JOINER CABLE

102125JCSccllld

DRAWN BY: J.Y.	APPROVED: D.H.	102125JCS.8
DATE: 27–NOV–08	SCALE: N.T.S.	